



B 58_B 58 MX

PRODOTTO VINCENTE ADDOLCITORE ANTIALGA BATTERIOSTATICO LINEA B 58 | B 58 MX

GRADI FRANCESI	GRADI TEDESCHI	LITRI TRATTATI
9° Fr	5 KH	14.000
18° Fr	10 KH	7.000
27° Fr	15 KH	4.666
36° Fr	20 KH	3.500
45° Fr	25 KH	2.800

GRADI FRANCESI 18° FR | GRADI TEDESCHI 10 KH

■ Sistemi pratici ed economici per "addolcire" l'acqua a base di una innovativa miscela di **RESINA** che consente di sottrarre dall'acqua calcare, metalli pesanti o impurità di ostacolo alla totale salubrità delle bevande nel settore del vending ed HO.RE.CA. Di ampia autonomia, la loro **FORMULA BREVETTATA** garantisce il rispetto degli standard e delle normative igienico-sanitarie

■ Practical and economic system to "soften" water, based on an innovative blend of **RESIN** that allows the removal of heavy metals or impurities from lime water impede the complete salubrity of beverages found in vending machines in the HO.RE.CA. Their patented formula, featuring broad autonomy, guarantees the full **OBSERVATION OF ALL STANDARDS** accorded in sanitary regulation.





LINEA

B 58

B 58 MX

🇮🇹 **SCHEMA TECNICA**

🇬🇧 **TECHNICAL DATA**

DIMENSIONI E PESO_150 mm x 439 mm – 3 Kg

MATERIALI STRUTTURA_Polipropilene

FUNZIONAMENTO_Verticale e/o orizzontale

PRESSIONE MAX_8 atmosfere

TEMPERATURA DI LAVORO_+5°C / +40°C

GRADO DI FILTRAZIONE_150 microns

pH7_Neutro

BATTERIOSTATICITÀ_Resina argentizzata

RIMOZIONE METALLI PESANTI_[Cr³⁺ Al³⁺ Cu²⁺ Pb²⁺ Fe²⁺ Zn²⁺ Ni²⁺ Cd²⁺ H₂AsO₄ SeO₃₂₋ SbO₂₋ MoO₄₂₋ VO³ PO₄₃₋]

ADDOLCIMENTO_Durezza carbonatica

ALIMENTARIETÀ_18 mesi dalla data d'installazione

PRODOTTO IN_Italia

SMALTIMENTO_Rifiuto SPECIALE NON PERICOLOSO

CODICE SMALTIMENTO_C.E.R. 19.09.05

REACH_Conforme

BYPASS_Opzionale

TIPOLOGIA_Addolcitore cartuccia usa e getta

CONFORMITÀ_D.M. MINISTERO SALUTE 174/2007
D.P.R. 236/1988 e D.L. 31/2001
98/83/CEE

DIMENSIONS-WEIGHT_(D x H) 150 mm x 439 mm – 3 Kg

STRUCTURE MATERIAL_Polypropylene

FUNCTIONING_Vertical / Horizontal

Max PRESSURE_8 ATM

OPERATING TEMPERATURE_+5°C / +40°C

FILTERING_150 microns

pH7_Neutral

BACTERIOSTATIC CONDITION_Silver ions

HEAVY METAL REMOVAL_[Cr³⁺ Al³⁺ Cu²⁺ Pb²⁺ Fe²⁺ Zn²⁺ Ni²⁺ Cd²⁺ H₂AsO₄ SeO₃₂₋ SbO₂₋ MoO₄₂₋ VO³ PO₄₃₋]

SOFTENING_Carbonate hardness

FOOD SAFETY_18 months from installation date

MADE in_Italy

DISPOSAL_Special but NOT harmful waste

WASTE CODE_C.E.R. 19.09.05

REACH_Conforming

BYPASS_Optional

TYPE_Disposable cartridge softener

CONFORMITY_D.M. MINISTERO SALUTE 174/2007
D.P.R. 236/1988 – D.L. 31/2001
98/83/CEE

AUTONOMIA

VALORI MERCK	GRADI FRANCESI	GRADI TEDESCHI	LITRI TRATTATI	
			B 58	B 58 MX
● ● ● ● ●	9° Fr	5 KH	14000	11400
● ● ● ● ●	18° Fr	10 KH	7000	5700
● ● ● ● ●	27° Fr	15 KH	4660	3800
● ● ● ● ●	36° Fr	20 KH	3500	2850
● ● ● ● ●	45° Fr	25 KH	2800	2280

AUTONOMY

MERCK	FRENCH DEGREES	GERMAN DEGREES	TREATED LITRES	
			B 58	B 58 MX
● ● ● ● ●	9° Fr	5 KH	14000	11400
● ● ● ● ●	18° Fr	10 KH	7000	5700
● ● ● ● ●	27° Fr	15 KH	4660	3800
● ● ● ● ●	36° Fr	20 KH	3500	2850
● ● ● ● ●	45° Fr	25 KH	2800	2280